

Gas fireplace with surround in handmade majolica. Also available in double-sided version.

AVAILABLE COLOURS:

iron-grey, mocha-brown, ivory, snow white

SURROUND WEIGHT: 40 kg

GAS BURNING (NATURAL GAS OR LPG) IG 120

STOVE: in grey enamelled steel
 FIREBOX: in Aluker®
 GLASS: ceramic heat resistant up to 750°C
 FUNCTION CONTROL: remote control
 CERAMIC LOGS: standard supply
 HEATING: convection and radiation
 CEILING FLUE GAS OUTLET:
 concentric pipe Ø 10/15 cm
 WALL FLUE GAS OUTLET:
 concentric pipe Ø 13/20 cm
 FIREBOX HEAT OUTPUT: 11.5 kW (Natural gas)
 10.5 kW (LPG)
 THERMAL EFFICIENCY: 80% (Natural gas)
 77% (LPG)
 CONSUMPTION AT RATED HEAT OUTPUT:
 1.1 m³/h (Natural gas)
 790 g/h (LPG)
 WEIGHT: 135 kg
 RATED HEAT OUTPUT: 8.3 kW (Natural gas)
 7.3 kW (LPG)
 TYPE-EXAMINATION: EC certification E0780
 OPTIONAL ACCESSORIES: river pebbles

GAS BURNING (NATURAL GAS OR LPG) IG 120B

STOVE: in grey enamelled steel
 FIREBOX: in Aluker®
 GLASS: ceramic heat resistant up to 750°C
 FUNCTION CONTROL: remote control
 CERAMIC LOGS: standard supply
 HEATING: convection and radiation
 CEILING FLUE GAS OUTLET:
 concentric pipe Ø 10/15 cm
 WALL FLUE GAS OUTLET:
 concentric pipe Ø 13/20 cm
 FIREBOX HEAT OUTPUT: 11.5 kW (Natural gas)
 10.5 kW (LPG)
 THERMAL EFFICIENCY: 80% (Natural gas)
 77% (LPG)
 CONSUMPTION AT RATED HEAT OUTPUT:
 1.1 m³/h (Natural gas)
 790 g/h (LPG)
 WEIGHT: 130 kg
 RATED HEAT OUTPUT: 8.3 kW (Natural gas)
 7.3 kW (LPG)
 TYPE-EXAMINATION: EC certification E0780
 OPTIONAL ACCESSORIES: river pebbles

WOOD BURNING ME 120/48

STOVE: in enamelled steel
 FIREBOX: in Aluker®
 GRATE: in Aluker® with cast iron grid
 DOOR: rise n'fall in enamelled steel
 with glass ceramic heat resistant up to 750°C,
 may also be opened as hinged door for
 cleaning
 PRIMARY AIR: adjustable by hand
 SECONDARY AIR: pre-determined
 SMOKE DAMPER: automatic and adjustable
 ASH DRAWER: removable
 HEATING: natural convection
 or forced air circulation by
 Multifuoco System® on request
 FLUE GAS OUTLET: Ø 25 cm
 MINIMUM DRAUGHT: 11 Pa Min.
 RATED HEAT OUTPUT: 16.5 kW
 THERMAL EFFICIENCY: 75.5%
 CONSUMPTION AT RATED HEAT OUTPUT: 4.8 kg/h
 WEIGHT: 355 kg
 Laboratory measurements were made using
 beech wood with moisture content below 20%
 TYPE-EXAMINATION: declaration of conformity
 in accordance with directive 89/106/EEC
 Type approval in accordance with EN13230
 OPTIONAL ACCESSORIES:
 • ventilation kit Multifuoco System®
 with automatic or manual switching
 on and off and 4-speed radio control.
 Flow rate: 220 m³/h without ducting
 230 V-50Hz - 47W

SIZE:

	IG 120	IG 120B	ME 120/48
A	38.5	38.5	59.5
B	121	121	123.5
C	12.5	19.5	19.5
Ø	15-20	15-20	25

