

Gas or wood-burning fireplace with handmade majolica surround.

AVAILABLE COLOURS:  
iron-grey, orange, antiqued copper

SURROUND WEIGHT: 24 kg

#### GAS BURNING (NATURAL GAS OR LPG) IG 70

STOVE: in grey enamelled steel  
FIREBOX: in Aluker®  
GLASS: ceramic heat resistant up to 750°C  
FUNCTION CONTROL: remote control  
CERAMIC LOGS: standard supply  
HEATING: convection and radiation  
FLUE GAS OUTLET: concentric pipe Ø 10/15 cm  
FIREBOX HEAT OUTPUT: 8.3 kW (Natural gas)  
8.5 kW (LPG)  
THERMAL EFFICIENCY: 80% (Natural gas)  
75% (LPG)  
CONSUMPTION AT RATED HEAT OUTPUT:  
0.79 m³/h (Natural gas)  
640 g/h (LPG)

WEIGHT: 75 kg  
RATED HEAT OUTPUT: 6 kW (Natural gas)  
5.7 kW (LPG)  
TYPE-EXAMINATION: EC certification E0780  
OPTIONAL ACCESSORIES: river pebbles

#### WOOD BURNING 600 HT

STOVE: in black enamelled steel;  
also available in version with door frame  
in shot-peened stainless steel  
FIREBOX: Aluker®  
GRATE: in cast iron  
DOOR: rise n'fall with glass ceramic  
heat resistant up to 750°C, may also be  
opened as hinged door for cleaning  
PRIMARY AIR: pre-determined  
SECONDARY AIR: pre-determined  
SMOKE DAMPER: adjustable externally  
ASH DRAWER: removable  
HEATING: natural convection  
or forced air circulation by  
Multifuoco System® on request  
FLUE GAS OUTLET: Ø 20 cm  
MINIMUM DRAUGHT: 10 Pa Min.  
RATED HEAT OUTPUT: 10 kW  
THERMAL EFFICIENCY: 74.20%  
CONSUMPTION AT RATED HEAT OUTPUT: 3.5 kg/h  
WEIGHT: 190 kg

Laboratory measurements were made using  
beech wood with moisture content below 20%  
TYPE-EXAMINATION: declaration of conformity  
in accordance with directive 89/106/EEC  
Type approval in accordance with EN13229  
OPTIONAL ACCESSORIES:

- ventilation kit Multifuoco System®  
with automatic or manual switching  
on and off and 4-speed radio control.  
Flow rate: 220 m³/h without ducting  
230 V-50Hz - 47W

#### WOOD BURNING MA 260

STOVE: in enamelled steel  
FIREBOX: in Aluker®  
GRATE: in cast iron  
DOOR: (optional hinged opening door  
in enamelled steel with glass ceramic  
heat resistant up to 750°C)  
PRIMARY AIR: not present  
(adjustable by hand)  
SECONDARY AIR: not present  
(adjustable by hand)  
SMOKE DAMPER: adjustable externally  
ASH DRAWER: removable  
HEATING: convection  
and radiation  
FLUE GAS OUTLET: Ø 20 cm  
MINIMUM DRAUGHT: 10 (12) Pa Min.  
RATED HEAT OUTPUT: 8 kW  
THERMAL EFFICIENCY: 51 (59) %  
CONSUMPTION AT RATED HEAT OUTPUT:  
3.6 (3.2) kg/h  
WEIGHT: 120 (135) kg

Laboratory measurements were made using  
beech wood with moisture content below 20%  
TYPE-EXAMINATION: declaration of conformity  
in accordance with directive 89/106/EEC  
Type approval in accordance with EN13229  
OPTIONAL ACCESSORIES:

- glass door kit
- log grate

NOTE: features and technical data  
related to the version with glass door kit  
are given in brackets

SIZE:

	IG 70	600 HT	MA 260
A	36	62	59.5
B	74	84	80
C	11	27.5	17.5
Ø	15	20	20

