

Gas or wood-burning fireplace with handmade majolica surround.

AVAILABLE COLOURS:
glossy grey, plum, lime white

SURROUND WEIGHT: 53 kg

GAS BURNING (NATURAL GAS OR LPG) IG 70

STOVE: in grey enamelled steel
 FIREBOX: in Aluker®
 GLASS: ceramic heat resistant up to 750°C
 FUNCTION CONTROL: remote control
 CERAMIC LOGS: standard supply
 HEATING: convection and radiation
 FLUE GAS OUTLET: concentric pipe Ø 10/15 cm
 FIREBOX HEAT OUTPUT: 8.3 kW (Natural gas)
 8.5 kW (LPG)
 THERMAL EFFICIENCY: 80% (Natural gas)
 75% (LPG)
 CONSUMPTION AT RATED HEAT OUTPUT:
 0.79 m³/h (Natural gas)
 640 g/h (LPG)
 WEIGHT: 75 kg
 RATED HEAT OUTPUT: 6 kW (Natural gas)
 5.7 kW (LPG)
 TYPE-EXAMINATION: EC certification E0780
 OPTIONAL ACCESSORIES: river pebbles

WOOD BURNING 600 HT

STOVE: in black enamelled steel;
 also available in version with door frame
 in shot-peened stainless steel
 FIREBOX: Aluker®
 GRATE: in cast iron
 DOOR: rise n'fall with glass ceramic
 heat resistant up to 750°C, may also be
 opened as hinged door for cleaning
 PRIMARY AIR: pre-determined
 SECONDARY AIR: pre-determined
 SMOKE DAMPER: adjustable externally
 ASH DRAWER: removable
 HEATING: natural convection
 or forced air circulation by
 Multifuoco System® on request
 FLUE GAS OUTLET: Ø 20 cm
 MINIMUM DRAUGHT: 10 Pa Min.
 RATED HEAT OUTPUT: 10 kW
 THERMAL EFFICIENCY: 74.20%
 CONSUMPTION AT RATED HEAT OUTPUT: 3.5 kg/h
 WEIGHT: 190 kg
 Laboratory measurements were made using
 beech wood with moisture content below 20%
 TYPE-EXAMINATION: declaration of conformity
 in accordance with directive 89/106/EEC
 Type approval in accordance with EN13229
 OPTIONAL ACCESSORIES:
 • ventilation kit Multifuoco System®
 with automatic or manual switching
 on and off and 4-speed radio control.
 Flow rate: 220 m³/h without ducting
 230 V-50Hz - 47W

WOOD BURNING MA 260

STOVE: in enamelled steel
 FIREBOX: in Aluker®
 GRATE: in cast iron
 DOOR: (optional hinged opening door
 in enamelled steel with glass ceramic
 heat resistant up to 750°C)
 PRIMARY AIR: not present
 (adjustable by hand)
 SECONDARY AIR: not present
 (adjustable by hand)
 SMOKE DAMPER: adjustable externally
 ASH DRAWER: removable
 HEATING: convection and radiation
 FLUE GAS OUTLET: Ø 20 cm
 MINIMUM DRAUGHT: 10 (12) Pa Min.
 RATED HEAT OUTPUT: 8 kW
 THERMAL EFFICIENCY: 51 (59) %
 CONSUMPTION AT RATED HEAT OUTPUT:
 3,6 (3,2) kg/h
 WEIGHT: 120 (135) kg
 Laboratory measurements were made using
 beech wood with moisture content below 20%
 TYPE-EXAMINATION: declaration of conformity
 in accordance with directive 89/106/EEC
 Type approval in accordance with EN13229
 OPTIONAL ACCESSORIES:
 • glass door kit
 • log grate
 NOTE: features and technical data
 related to the version with glass door kit
 are given in brackets

SIZE:

	IG 70	600 HT	MA 260
A	42	62	60
B	73	84	80
C	11	25	18
Ø	15	20	20

