

Gas or wood-burning fireplace. Handmade majolica surround with hearth, lintel. Supports and trims in shot-peened steel. The tobacco-brown and grey-brown versions are embellished with hand-crafted ornamentation.

**AVAILABLE COLOURS:**

iron-grey, decorated grey-brown, decorated light tobacco-brown, mocha-brown, ivory, snow white

**SURROUND WEIGHT:** 175 kg

**GAS BURNING (NATURAL GAS OR LPG) IG 90**

STOVE: in grey enamelled steel

GLASS: ceramic heat resistant up to 750°C

FUNCTION CONTROL: remote control

CERAMIC LOGS: standard supply

HEATING: convection and radiation

FLUE GAS OUTLET: concentric pipe Ø 10/15 cm

FIREBOX HEAT OUTPUT: 9.5 kW (Natural gas)

9.5 kW (LPG)

THERMAL EFFICIENCY: 80% (Natural gas)

75% (LPG)

CONSUMPTION AT RATED HEAT OUTPUT:

0.90 m<sup>3</sup>/h (Natural gas)

720 g/h (LPG)

WEIGHT: 105 kg

RATED HEAT OUTPUT: 6.8 kW (Natural gas)

6.4 kW (LPG)

TYPE-EXAMINATION: EC certification E0780

OPTIONAL ACCESSORIES: river pebbles

**WOOD BURNING ME 90/44**

STOVE: in enamelled steel

FIREBOX: in Aluker®

GRATE: in Aluker® with cast iron grid

DOOR: rise n'fall in enamelled steel

with glass ceramic heat resistant up to 750°C,

may also be opened as hinged door for

cleaning

PRIMARY AIR: adjustable by hand

SECONDARY AIR: pre-determined

SMOKE DAMPER: automatic and adjustable

ASH DRAWER: removable

HEATING: natural convection

or forced air circulation by

Multifuoco System® on request

FLUE GAS OUTLET: Ø 25 cm

MINIMUM DRAUGHT: 11 Pa Min.

RATED HEAT OUTPUT: 14 kW

THERMAL EFFICIENCY: 71.5

CONSUMPTION AT RATED HEAT OUTPUT: 4.6 kg/h

WEIGHT: 335 kg

Laboratory measurements were made using

beech wood with moisture content below 20%

TYPE-EXAMINATION: declaration of conformity

in accordance with directive 89/106/EEC

Type approval in accordance with EN13229

OPTIONAL ACCESSORIES:

- ventilation kit Multifuoco System® with automatic or manual switching on and off and 4-speed radio control. Flow rate: 220 m<sup>3</sup>/h without ducting 230 V-50Hz - 47W

**SIZE:**

	IG 90	ME 90/44
A	24	43
B	93	95,5
C	12,5	19,5
Ø	15	25

